NSN 4820-00-497-2348

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-497-2348

Pipe Size Accommodated:
0.250 inches 2nd end
Thread Direction:
Right-hand 2nd end
Flow Control Device:
Poppet
Disk Loading Method:
Spring
Maximum Operating Temp:
165.0 degrees fahrenheit single response
Connection Style:
Flared (tube) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded external tube 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
18 2nd end
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Thread Size:
0.250 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Stainless steel flow control device
Media For Which Designed:
Oil, lubricating, diester base single response
Surface Treatment:
Passivate
Style Designator:
Straight thru
Thread Series Designator:
Anpt 2nd end
Furnished Items And Quantity:
1 cap and 1 chain
Shelf Life:
N/a

NSN 4820-00-497-2348

Check Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A530b0