

View Online at <https://aerobasegroup.com/nsn/4820-00-497-4648>

**Thread Class:**

3a 1st end

**Thread Direction:**

Right-hand 1st end

**Flow Control Device:**

Cone

**Disk Loading Method:**

Spring

**Connection Style:**

Flared (tube) 1st end

**Connection Type:**

Threaded external tube 1st end

**Mounting Position:**

Horizontal or vertical

**Thready Qty Per Inch (tpi):**

20 1st end

**Maximum Operating Pressure:**

1500.0 pounds per square inch single response

**Thread Size:**

0.438 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Outside Diameter Tube Accommodated:**

0.250 inches 1st end

**Special Features:**

1.2 gpm rated flow capacity

**Media For Which Designed:**

Hydraulic fluid, petroleum base single response

**Style Designator:**

Straight thru

**Test Data Document:**

81349-mil-v-5524 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf 1st end

**Specification Or Standard:**

A style and 1500 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A530b0