NSN 4820-00-497-4648

Check Valve - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/4620-00-497-4646
Thread Class:
3a 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Cone
Disk Loading Method:
Spring
Connection Style:
Flared (tube) 1st end
Connection Type:
Threaded external tube 1st end
Mounting Position:
Horizontal or vertical
Thready Qty Per Inch (tpi):
20 1st end
Maximum Operating Pressure:
1500.0 pounds per square inch single response
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Special Features:
1.2 gpm rated flow capacity
Media For Which Designed:
Hydraulic fluid, petroleum base single response
Style Designator:
Straight thru
Test Data Document:
81349-mil-v-5524 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unf 1st end
Specification Or Standard:
A style and 1500 class
Shelf Life:
N/a
Unit Of Measure:
.

Yes - demil/mli

Demilitarization:

NSN 4820-00-497-4648

Check Valve - Page 2 of 2



Fiig:

A530b0