## NSN 4820-00-499-2585

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-499-2585

View Online at https://aerobasegroup.com/nsn/4820-00-499-2585
Flow Control Device:
Poppet
Bolt Hole Quantity:
4 1st end
Maximum Operating Temp:
450.0 degrees fahrenheit single response
Connection Style:
Beaded (hose) 2nd end
Width:
2.440 inches 1st end
Length:
2.400 inches 1st end
Valve Operation Method:
Automatic
Flange Shape:
Rectangular with holes 1st end
Connection Type:
Unthreaded external hose 2nd end
Mounting Position:
Horizontal
Maximum Operating Pressure:
90.0 pounds per square inch single response
Thickness:
0.250 inches 1st end
Bolt Hole Diameter:
0.285 inches 1st end
Center To Center Distance Between Bolt Holes Along Length:
1.812 inches 1st end
Center To Center Distance Between Bolt Holes Along Width:
1.812 inches 1st end
Flange Face Design:
Plain 1st end
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-/6, alloy 2024 federal specification single material response
Media For Which Designed:
Air single response
Surface Treatment:
Anodize
Surface Treatment Specification:

Mil-a-8625, type 2 military specification single treatment response

## NSN 4820-00-499-2585

Check Valve - Page 2 of 2



Style Designator:
Straight thru
Shelf Life:
N/a
Unit Of Measure:
 Demilitarization:
Demilitarization: Yes - demil/mli

Mil-std (military Standard):

Mil-a-8625 spec.