

NSN 4820-00-516-1109 Lift-check Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-516-1109 **Thread Class:** 2a all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Integral **Maximum Operating Temp:** 275.0 degrees fahrenheit single response **Connection Style:** Plain (tube) all ends **Valve Operation Method:** Manual **Connection Type:** Threaded external tube all ends **Mounting Facility:** Threaded fastener **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.500 inches all ends Seat Angle: 12.5 degrees all ends

Outside Diameter Tube Accommodated:

0.312 inches all ends

Material:

Aluminum alloy seat

Media For Which Designed:

Hydraulic fluid, mineral base single response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ms 2400-3 assn standard single treatment response

Style Designator:

Straight thru

Thread Series Designator:

Unf all ends

NSN 4820-00-516-1109

Lift-check Valve - Page 2 of 2



_			-		
C	hΔ	Iŧ.		.ife	
J			_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0