NSN 4820-00-516-3431

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-516-3431 **Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Disk Loading Method:** Spring **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Flared (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded external tube all ends **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 14 all ends **Maximum Operating Pressure:** 1500.0 pounds per square inch single response **Thread Size:** 0.875 inches all ends Seat Angle: 37.0 degrees all ends **Opening Pressure Setting:** 18.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.625 inches all ends Material: Steel flow control device Media For Which Designed: Fuel/oil, hydrocarbon single response **Style Designator:** Straight through note: to be used for valve bodies of one section only. **Thread Series Designator:** Unf all ends Shelf Life:

N/a **Unit Of Measure:**

NSN 4820-00-516-3431

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0