## NSN 4820-00-516-3560



Safety Relief Valve - Page 1 of 2	Gro
View Online at https://aerobasegroup.com/nsn/4820-00-516-3560	
Pipe Size Accommodated:	
0.750 inches 1st end	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Flow Control Device:	
Poppet	
Bonnet Type:	
Inside screw	
Bonnet Attachment Method:	
Integral	
Disk Loading Method:	
Spring	
Valve Discharge Flow Rate:	
16.0 gallons per minute	
Maximum Operating Temp:	
160.0 degrees fahrenheit single response	
Connection Style:	
Gasket sea (boss) 1st end	
Valve Operation Method:	
Automatic	
Connection Type:	
Threaded internal boss 1st end	
Mounting Facility:	
Threaded fastener	
Thready Qty Per Inch (tpi):	
12 1st end	
Adjustable Pressure Range:	
+1000.0/+2300.0 pounds per square inch	
Maximum Operating Pressure:	

2300.0 pounds per square inch single response

**Thread Size:** 

1.062 inches 1st end

Seat Angle:

45.0 degrees 1st end

Material:

Stainless steel stem

**Media For Which Designed:** 

Hydraulic fluid, phosphate-ester base single response

Style Designator:

Angle w/offset

## NSN 4820-00-516-3560

Safety Relief Valve - Page 2 of 2



Thread Series Designator:	
Un 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	

No

Fiig:

A046b0