## NSN 4820-00-516-3592



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-516-3592 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Bonnet Type:** Inside screw **Bonnet Attachment Method:** Integral **Disk Loading Method:** Spring **Maximum Operating Temp:** 165.0 degrees fahrenheit single response

**Connection Style:** 

Gasket sea (boss) all ends

**Valve Operation Method:** 

Automatic

**Connection Type:** 

Threaded internal boss all ends

**Features Provided:** 

Pressure tight outlet side

Adjustable Pressure Range:

+1000.0/+4100.0 pounds per square inch

**Maximum Operating Pressure:** 

4100.0 pounds per square inch single response

**Thread Size:** 

0.437 inches all ends

Material:

Nickel alloy body

Media For Which Designed:

Oil, hydraulic single response

**Style Designator:** 

Angle

**Thread Series Designator:** 

Unf all ends

**Specification Or Standard:** 

Single type and ab class

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 4820-00-516-3592

Safety Relief Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A046b0