## NSN 4820-00-516-4403

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-516-4403

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Poppet
Bonnet Type:
Packing retaining
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
2.5 gallons per minute
Maximum Operating Temp:
180.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss 1st end
Thready Qty Per Inch (tpi):
20 1st end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Opening Pressure Setting:
1050.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Special Features:
Reverse flow
Material:
Stainless steel stem
Style Designator:
Straight thru
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 4820-00-516-4403

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0