NSN 4820-00-516-4407

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-516-4407 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Maximum Operating Temp:** 100.0 degrees fahrenheit single response **Connection Style:** Flar (tube) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube 1st end **Mounting Facility:** Threaded fastener Thready Qty Per Inch (tpi): 18 1st end **Adjustable Pressure Range:** +1350.0/+4500.0 pounds per square inch **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.562 inches 1st end **Outside Diameter Tube Accommodated:** 0.375 inches 1st end Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base single response

Style Designator: Straight through w/baffle **Thread Series Designator:** Unf 1st end Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 4820-00-516-4407

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0