NSN 4820-00-528-2359

Check Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-528-2359

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Cone

Connection Style:

Flared (tube) 1st end

Connection Type:

Threaded external tube 1st end

Mounting Position:

Horizontal or vertical

Thready Qty Per Inch (tpi):

20 1st end

Maximum Operating Pressure:

450.0 pounds per square inch single response

Thread Size:

0.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Outside Diameter Tube Accommodated:

0.312 inches 1st end

Special Features:

Third end 1/4 anpt

Media For Which Designed:

Oxygen, gaseous single response

Test Data Document:

81349-mil-v-7908 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf 1st end

Specification Or Standard:

C style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A530b0