NSN 4820-00-528-2835

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-528-2835

| Thread Class: |
|--|
| 3b all ends |
| Thread Direction: |
| Right-hand all ends |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside screw |
| Bonnet Attachment Method: |
| Integral |
| Disk Loading Method: |
| Spring |
| Valve Discharge Flow Rate: |
| 7.0 gallons per minute |
| Maximum Operating Temp: |
| 160.0 degrees fahrenheit single response |
| Connection Style: |
| Gasket sea (boss) all ends |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded internal boss all ends |
| Features Provided: |
| Pressure tight outlet side |
| Maximum Operating Pressure: |
| 975.0 pounds per square inch single response |
| Thread Size: |
| 0.562 inches all ends |
| Opening Pressure Setting: |
| 975.0 pounds per square inch |
| Outside Diameter Tube Accommodated: |
| 0.375 inches all ends |
| Special Features: |
| Reverse flow |
| Material: |
| Stainless steel stem |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Style Designator: |
| Straight thru |
| Thread Series Designator: |
| Unf all ends |

NSN 4820-00-528-2835

Safety Relief Valve - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0