NSN 4820-00-528-2835

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-528-2835

Thread Class:
3b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
7.0 gallons per minute
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Gasket sea (boss) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal boss all ends
Features Provided:
Pressure tight outlet side
Maximum Operating Pressure:
975.0 pounds per square inch single response
Thread Size:
0.562 inches all ends
Opening Pressure Setting:
975.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.375 inches all ends
Special Features:
Reverse flow
Material:
Stainless steel stem
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Style Designator:
Straight thru
Thread Series Designator:
Unf all ends

NSN 4820-00-528-2835

Safety Relief Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0