## NSN 4820-00-528-2836

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-528-2836 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: Disk **Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 7.0 gallons per minute **Connection Style:** Plain, optional en (pipe) 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 8 1st end Adjustable Pressure Range: +1000.0/+2100.0 pounds per square inch **Maximum Operating Pressure:** 2100.0 pounds per square inch single response **Thread Size:** 0.562 inches 1st end **Outside Diameter Tube Accommodated:** 0.375 inches 1st end Material: Stainless steel seat Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Style Designator:** Straight thru **Supplementary Features:** Appl to c-135/kc-135 acft **Thread Series Designator:** Unf 1st end Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 4820-00-528-2836

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0