NSN 4820-00-528-2838

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-528-2838 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 32.0 gallons per minute **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 1st end **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 12 1st end **Adjustable Pressure Range:** +2100.0/+3500.0 pounds per square inch **Maximum Operating Pressure:** 3500.0 pounds per square inch single response **Thread Size:** 1.062 inches 1st end Material: Stainless steel stem Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Style Designator:** Straight thru **Supplementary Features:** Applicable to acft, type c-135 and kc-135 **Thread Series Designator:** Unj 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 4820-00-528-2838

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0