NSN 4820-00-529-1495

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-529-1495

Pipe Size Accommodated:
0.375 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Poppet
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Bonnet packing and pressure tight outlet side
Thready Qty Per Inch (tpi):
18 all ends
Adjustable Pressure Range:
+500.0/+4000.0 pounds per square inch
Maximum Operating Pressure:
4000.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
Material:
Steel flow control device and rubber butadiene-acrylonitrile class nbr flow control device
Media For Which Designed:
Water-oil-gas single response
Surface Treatment:
Anodize
Style Designator:
Angle
Thread Series Designator:
Nptf all ends
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-529-1495

Safety Relief Valve - Page 2 of 2



Demilitarization:

No

Fiig:

A046b0