

View Online at <https://aerobasegroup.com/nsn/4820-00-529-1965>

Flow Control Device:

Disk

Bonnet Type:

Exposed spring

Bonnet Attachment Method:

Bolted

Disk Loading Method:

Spring

Renewable Seat Ring Type:

Threaded

Bolt Hole Quantity:

6 2nd end

Maximum Operating Temp:

400.0 degrees fahrenheit single response

Valve Operation Method:

Automatic

Flange Shape:

Round with holes 2nd end

Connection Type:

Flange 1st end

Adjustable Pressure Range:

+1700.0/+2400.0 pounds per square inch

Maximum Operating Pressure:

2400.0 pounds per square inch single response

Outside Diameter:

5.562 inches 2nd end

Thickness:

1.750 inches 1st end

Bolt Hole Diameter:

0.938 inches 1st end

Bolt Circle Diameter:

6.500 inches 1st end

Flange Face Design:

Plain 2nd end

Raised Face Height:

0.250 inches 1st end

Raised Face Diameter:

5.500 inches 1st end

Material:

Steel stem

Media For Which Designed:

Water, fresh single response

Style Designator:

Angle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0