NSN 4820-00-529-3155

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-529-3155 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Disk Loading Method:** Weight **Maximum Operating Temp:** 250.0 degrees fahrenheit single response **Connection Style:** Flare (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube all ends **Mounting Position:** Horizontal or vertical **Maximum Operating Pressure:** 175.0 pounds per square inch single response **Thread Size:** 0.562 inches all ends Seat Angle: 60.0 degrees 1st end **Outside Diameter Tube Accommodated:** 0.375 inches all ends **Special Features:** Proof pressure 350.0 psi, burst pressure 700.0 psi, cracking pressure 1.0 psi, pressure drop 2.5 psi max Material: Rubber synthetic flow control device Media For Which Designed: Hydraulic fluid, petroleum base 2nd response **Surface Treatment:** Anodize **Style Designator:** Straight thru **Thread Series Designator:** Unf all ends Shelf Life: N/a

Unit Of Measure:

NSN 4820-00-529-3155

Check Valve - Page 2 of 2



Demi			

No

Fiig:

A530b0