NSN 4820-00-529-3640

Check Valve - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/4820-00-529-3640

3b all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Cone
Disk Loading Method:
Spring
Maximum Operating Temp:
1560.0 degrees fahrenheit single response
Connection Style:
Inverted flare (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal tube all ends
Mounting Position:
Horizontal
Thready Qty Per Inch (tpi):
12 all ends
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
1.500 inches all ends
Seat Angle:
60.0 degrees 1st end
Outside Diameter Tube Accommodated:
0.750 inches all ends
Material:
Aluminum alloy
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Style Designator:
Straight thru
Thread Series Designator:
Un all ends
Specification Data:
81349-mil-v-5524 government specification
Specification Or Standard:
3000 class
Shelf Life:
N/a

NSN 4820-00-529-3640

Check Valve - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A530b0