

View Online at <https://aerobasegroup.com/nsn/4820-00-529-3926>

**Thread Class:**

3b all ends

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Cone

**Disk Loading Method:**

Spring

**Maximum Operating Temp:**

160.0 degrees fahrenheit single response

**Connection Style:**

Inverted flare (tube) all ends

**Valve Operation Method:**

Automatic

**Connection Type:**

Threaded internal tube all ends

**Mounting Position:**

Horizontal or vertical

**Maximum Operating Pressure:**

3000.0 pounds per square inch single response

**Thread Size:**

0.750 inches all ends

**Seat Angle:**

60.0 degrees all ends

**Outside Diameter Tube Accommodated:**

0.500 inches all ends

**Media For Which Designed:**

Hydraulic fluid, phosphate-ester base single response

**Style Designator:**

Straight thru

**Test Data Document:**

81349-mil-v-5524 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf all ends

**Specification Or Standard:**

C style and 3000 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A530b0