

View Online at <https://aerobasegroup.com/nsn/4820-00-529-3936>

**Thread Class:**

3b

**End Connection Quantity:**

3

**End Application:**

Applicable t.O. 9h8-14-140-3 fig 2; u/o code a

**Current Rating In Amps:**

0.5

**Valve Operation Method:**

Solenoid

**Connection Type:**

Threaded internal boss

**Features Provided:**

Continuous duty and manual override

**Maximum Operating Pressure And Media For Which Designed:**

3000.0 pounds per square inch hydraulic fluid, petroleum base

**Thread Size:**

0.750 inches

**Body Material:**

Aluminum alloy

**Maximum Operating Temperature And Media For Which Designed:**

250.0 degrees fahrenheit hydraulic fluid, petroleum base

**Voltage In Volts And Current Type:**

17.0 dc and 30.0 dc

**Flow Pattern Quantity:**

3

**Spool Position Quantity:**

2

**Spool Quantity:**

1

**Special Features:**

Manufacturers suggested name is solenoid operated three way selector valve; media fluid mil-h-5606; current consumption 0.5 amp, maximum at 24 vdc; pressure to actuate valve 100 psig ; port per ms33649, 1/2 inch tube connections; mounting hole (3) 0.203 to 0.228 inch diameter; ambient temp range -65 to +250 degrees feh; wt 1.31 lbs; major component parts: piston and sleeve assembly 26028, piston 26025, sleeve 26027, body 25471-8, cure dated items for repair parts kit 9672483-10, repair parts kit 9672484-10

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A506h0