NSN 4820-00-529-4177

Safety Relief Valve - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/4820-00-529-4177

3a 1st end
Thread Direction:
Right-hand 1st end
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Integral
Disk Loading Method:
Spring
Connection Style:
Flared (tube) 1st end
Connection Type:
Threaded external tube 1st end
Features Provided:
Valve stem lock shield and bonnet packing
Thready Qty Per Inch (tpi):
20 1st end
Maximum Operating Pressure:
3000.0 pounds per square inch single response
Thread Size:
0.437 inches 1st end
Seat Angle:
37.0 degrees 1st end
Opening Pressure Setting:
2800.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches 1st end
Material:
Aluminum alloy seat
Media For Which Designed:
Air single response
Surface Treatment:
Anodize
Style Designator:
Straight through w/baffle
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:

--

NSN 4820-00-529-4177

Safety Relief Valve - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A046b0