

View Online at <https://aerobasegroup.com/nsn/4820-00-529-4189>

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Offset Distance:

1.500 inches

Flow Control Device:

Poppet

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Threaded

Disk Loading Method:

Spring

Valve Discharge Flow Rate:

3.5 gallons per minute

Renewable Seat Ring Type:

Pressed-in

Maximum Operating Temp:

160.0 degrees fahrenheit single response

Connection Style:

Gasket sea (boss) 1st end

Valve Operation Method:

Automatic

Connection Type:

Threaded internal boss 2nd end

Mounting Facility:

Threaded fastener

Features Provided:

Bonnet packing

Thready Qty Per Inch (tpi):

18 1st end

Adjustable Pressure Range:

+2300.0/+3850.0 pounds per square inch

Maximum Operating Pressure:

3850.0 pounds per square inch single response

Thread Size:

0.562 inches 1st end

Special Features:

Designed for hydraulic fluid

Material:

Stainless steel seat

Surface Treatment:

Anodize

Style Designator:

Straight through w/offset

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A046b0