## NSN 4820-00-529-4232

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-529-4232

Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
7.0 gallons per minute
Connection Style:
Gasket sea (boss) 1st end
Connection Type:
Threaded internal boss 1st end
Mounting Facility:
Threaded fastener
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
18 1st end
Adjustable Pressure Range:
+100.0/+300.0 pounds per square inch
Maximum Operating Pressure:
300.0 pounds per square inch single response
Thread Size:
0.562 inches 1st end
Outside Diameter Tube Accommodated:
0.375 inches 1st end
Material:
Stainless steel seat
Media For Which Designed:
Hydraulic fluid, phosphate-ester base single response
Surface Treatment:
Anodize
Style Designator:
Straight thru
Supplementary Features:
Appl to acft, type c-135
Thread Series Designator:
Unf 1st end
Shelf Life:

## NSN 4820-00-529-4232

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A046b0