NSN 4820-00-529-4289

Check Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-529-4289

| view Online at https://aerobasegroup.com/nsn/4820- |
|----------------------------------------------------|
| Thread Class: |
| 3a 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Poppet |
| Disk Loading Method: |
| Spring |
| Maximum Operating Temp: |
| 250.0 degrees fahrenheit single response |
| Connection Style: |
| Flared (tube) 1st end |
| Valve Operation Method: |
| Automatic |
| Connection Type: |
| Threaded external tube 1st end |
| Mounting Position: |
| Horizontal or vertical |
| Thready Qty Per Inch (tpi): |
| 18 1st end |
| Maximum Operating Pressure: |
| 3000.0 pounds per square inch single response |
| Thread Size: |
| 0.562 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Outside Diameter Tube Accommodated: |
| 0.375 inches 1st end |
| Material: |
| Steel seat |
| Media For Which Designed: |
| Hydraulic fluid, mineral base single response |
| Style Designator: |
| Straight thru |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

No

NSN 4820-00-529-4289

Check Valve - Page 2 of 2

Fiig: A530b0

