NSN 4820-00-529-4525

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-529-4525

Pipe Size Accommodated: 0.375 inches 1st end Thread Direction: Right-hand 1st end Flow Control Device: Disk Bonnet Type: Inside screw Bonnet Attachment Method: Threaded Connection Style: Plain, optional en (pipe) 1st end Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Thread Direction: Right-hand 1st end Flow Control Device: Disk Bonnet Type: Inside screw Bonnet Attachment Method: Threaded Connection Style: Plain, optional en (pipe) 1st end Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Right-hand 1st end Flow Control Device: Disk Bonnet Type: Inside screw Bonnet Attachment Method: Threaded Connection Style: Plain, optional en (pipe) 1st end Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Flow Control Device: Disk Bonnet Type: Inside screw Bonnet Attachment Method: Threaded Connection Style: Plain, optional en (pipe) 1st end Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Disk Bonnet Type: Inside screw Bonnet Attachment Method: Threaded Connection Style: Plain, optional en (pipe) 1st end Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Bonnet Type: Inside screw Bonnet Attachment Method: Threaded Connection Style: Plain, optional en (pipe) 1st end Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Inside screw Bonnet Attachment Method: Threaded Connection Style: Plain, optional en (pipe) 1st end Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Bonnet Attachment Method: Threaded Connection Style: Plain, optional en (pipe) 1st end Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Threaded Connection Style: Plain, optional en (pipe) 1st end Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Connection Style: Plain, optional en (pipe) 1st end Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Plain, optional en (pipe) 1st end Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Valve Operation Method: Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Manual Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Connection Type: Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Threaded internal pipe 1st end Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Features Provided: Bonnet packing Thready Qty Per Inch (tpi):
Bonnet packing Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
40.4-4
18 1st end
Thread Size:
0.375 inches 1st end
Material:
Rubber flow control device or rubber synthetic flow control device
Surface Treatment:
Chromium
Style Designator:
Straight thru
Thread Series Designator:
Npt 1st end
Specification Or Standard:
D part and 2 type and 10 class and t13 style
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No.
Fiig:
A046b0