NSN 4820-00-529-5234

Safety Relief Valve - Page 1 of 2

Pipe Size Accommodated:

Bonnet Attachment Method:

0.500 inches all endsThread Direction:Right-hand all endsFlow Control Device:

Disk

Bonnet Type: Inside spring



View Online at https://aerobasegroup.com/nsn/4820-00-529-5234

Threaded
Disk Loading Method:
Spring
Maximum Operating Temp:
200.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Pressure tight outlet side
Thready Qty Per Inch (tpi):
14 all ends
Adjustable Pressure Range:
+251.0/+4000.0 pounds per square inch
Maximum Operating Pressure:
1100.0 pounds per square inch single response
Thread Size:
0.500 inches all ends
Material:
Steel stem
Media For Which Designed:
Water, fresh single response
Style Designator:
Angle
Thread Series Designator:
Npt all ends
Reference Number Differentiating Characteristics:
As differentiated by the pressure range and the valve size
Shelf Life:
N/a

NSN 4820-00-529-5234

Safety Relief Valve - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A046b0