NSN 4820-00-529-5496

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-529-5496 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Disk Loading Method:** Spring **Valve Discharge Flow Rate:** 20.0 gallons per minute **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Hydraulic **Connection Type:** Threaded internal boss 1st end **Mounting Facility:** Threaded fastener **Features Provided:** Valve stem lock shield and pressure tight outlet side Thready Qty Per Inch (tpi): 12 1st end **Thread Size:** 1.500 inches 1st end **Opening Pressure Setting:** 50.0 pounds per square inch Material: Aluminum alloy stem **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Style Designator:** Straight thru **Thread Series Designator:** Un 1st end Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 4820-00-529-5496

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.