## NSN 4820-00-530-9382

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-530-9382

Thread Direction:
Right-hand all ends

Poppet

**Bonnet Type:** 

Inside screw

**Bonnet Attachment Method:** 

Integral

**Disk Loading Method:** 

Flow Control Device:

Spring

**Maximum Operating Temp:** 

165.0 degrees fahrenheit single response

**Connection Style:** 

Plain (pipe) all ends

**Valve Operation Method:** 

Automatic

**Connection Type:** 

Threaded external pipe all ends

**Features Provided:** 

Pressure tight outlet side

Adjustable Pressure Range:

+17.0/+600.0 pounds per square inch

**Maximum Operating Pressure:** 

540.0 pounds per square inch 4th response

**Thread Size:** 

0.250 inches all ends

**Opening Pressure Setting:** 

95.0 pounds per square inch

Material:

Copper alloy

Media For Which Designed:

Oxygen, gaseous 2nd response

**Style Designator:** 

Straight thru

**Thread Series Designator:** 

Npt all ends

Shelf Life:

N/a

Unit Of Measure:

--

**Demilitarization:** 

No

## NSN 4820-00-530-9382

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0