

View Online at <https://aerobasegroup.com/nsn/4820-00-536-5296>

Thread Class:

3a 1st end

Thread Direction:

Right-hand 1st end

Flow Control Device:

Poppet

Bolt Hole Quantity:

3 2nd end

Connection Style:

Flareless 1st end

Valve Operation Method:

Manual

Flange Shape:

Triangular with holes 2nd end

Connection Type:

Threaded external tube 1st end

Thready Qty Per Inch (tpi):

16 1st end

Maximum Operating Pressure:

60.0 pounds per square inch 1st response

Thread Size:

0.750 inches 1st end

Seat Angle:

45.0 degrees 1st end

Bolt Circle Diameter:

1.750 inches 2nd end

Outside Diameter Tube Accommodated:

0.500 inches 1st end

Material:

Stainless steel flow control device

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Surface Treatment:

Anodize

Style Designator:

Angle

Test Data Document:

81349-mil-v-25023 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A530c0