NSN 4820-00-540-3468

Globe Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-540-3468

D. O. A. I.I.
Pipe Size Accommodated:
0.500 inches all ends
Flow Control Device:
Disk
Bonnet Type:
Inside screw
Bonnet Attachment Method:
Union
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
550.0 degrees fahrenheit 1st response
Connection Style:
Streamlined with two brazing rings all ends
Valve Operation Method:
Manual
Connection Type:
Unthreaded internal pipe all ends
Features Provided:
Features Provided: Bonnet packing
Bonnet packing
Bonnet packing Maximum Operating Pressure:
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material:
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material: Steel comp 420 seat
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material: Steel comp 420 seat Media For Which Designed:
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material: Steel comp 420 seat Media For Which Designed: Water-oil-gas 2nd response
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material: Steel comp 420 seat Media For Which Designed: Water-oil-gas 2nd response Style Designator:
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material: Steel comp 420 seat Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material: Steel comp 420 seat Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Shelf Life:
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material: Steel comp 420 seat Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Shelf Life: N/a
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material: Steel comp 420 seat Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Shelf Life: N/a
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material: Steel comp 420 seat Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Shelf Life: N/a Unit Of Measure:
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material: Steel comp 420 seat Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Shelf Life: N/a Unit Of Measure: Demilitarization: No
Bonnet packing Maximum Operating Pressure: 600.0 pounds per square inch 2nd response Material: Steel comp 420 seat Media For Which Designed: Water-oil-gas 2nd response Style Designator: Straight thru Shelf Life: N/a Unit Of Measure: Demilitarization: