## NSN 4820-00-540-3472

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-540-3472

| Pipe Size Accommodated:           |
|-----------------------------------|
| 0.375 inches 2nd end              |
| Thread Direction:                 |
| Right-hand 1st end                |
| Flow Control Device:              |
| Disk                              |
| Bonnet Type:                      |
| Inside spring                     |
| Bonnet Attachment Method:         |
| Integral                          |
| Disk Loading Method:              |
| Spring                            |
| Renewable Seat Ring Type:         |
| Threaded                          |
| Connection Style:                 |
| Plain, optional en (pipe) 1st end |
| Valve Operation Method:           |
| Automatic or manual               |
| Connection Type:                  |
| Threaded internal pipe 1st end    |
| Features Provided:                |
| Pressure tight outlet side        |
| Adjustable Pressure Range:        |
| +7.0/+25.0 pounds per square inch |
| Thread Size:                      |
| 0.375 inches 1st end              |
| Material:                         |
| Nickel alloy flow control device  |
| Style Designator:                 |
| Angle                             |
| Thread Series Designator:         |
| Npt 1st end                       |
| Shelf Life:                       |
| N/a                               |
| Unit Of Measure:                  |
|                                   |
| Demilitarization:                 |
| No                                |
| Fiig:                             |
| A046b0                            |