

View Online at <https://aerobasegroup.com/nsn/4820-00-541-0370>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Union

Renewable Seat Ring Type:

Threaded

Maximum Operating Temp:

425.0 degrees fahrenheit single response

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Maximum Operating Pressure:

300.0 pounds per square inch single response

Thread Size:

1.000 inches all ends

Special Features:

Valve size 1.000 in.

Material:

Steel seat

Material Specification:

Qq-c-390, alloy d4 federal specification single material response stem

Media For Which Designed:

Steam single response

Style Designator:

Straight thru

Test Data Document:

81349-mil-v-1187 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt all ends

Specification Data:

59646-mss sp-80 manufacturers standard

Specification Or Standard:

1 type and 300psi class and a end and 1.000 size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0