## NSN 4820-00-541-0435

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-541-0435

| ·····   |
|---|
| Thread Class:   |
| 3a 1st end  |
| Thread Direction:                                     |
| Right-hand 1st end                                    |
| Flow Control Device:                                  |
| Piston  |
| Disk Loading Method:                                  |
| Spring  |
| Valve Discharge Flow Rate:                            |
| 3.5 gallons per minute                                |
| Maximum Operating Temp:                               |
| 160.0 degrees fahrenheit single response              |
| Connection Style:                                     |
| Gasket sea (boss) 1st end                             |
| Connection Type:                                      |
| Threaded internal boss 1st end                        |
| Features Provided:                                    |
| Pressure tight outlet side                            |
| Thready Qty Per Inch (tpi):                           |
| 18 1st end  |
| Adjustable Pressure Range:                            |
| +200.0/+650.0 pounds per square inch                  |
| Maximum Operating Pressure:                           |
| 650.0 pounds per square inch single response          |
| Thread Size:  |
| 0.562 inches 1st end                                  |
| Media For Which Designed:                             |
| Hydraulic fluid, phosphate-ester base single response |
| Surface Treatment:                                    |
| Anodize   |
| Style Designator:                                     |
| Straight thru   |
| Thread Series Designator:                             |
| Unf 1st end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:                                      |
|   |
| Demilitarization:                                     |
| Yes - demil/mli                                       |
| Fiig:   |
|   |

A046b0