NSN 4820-00-541-0924

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-541-0924
Pipe Size Accommodated:
0.750 inches 2nd end
Thread Direction:
Right-hand 1st end
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Pressed-in
Maximum Operating Temp:
342.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) 1st end
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe 1st end
Features Provided:
Pressure tight outlet side
Maximum Operating Pressure:
110.0 pounds per square inch single response
Thread Size:
0.750 inches 2nd end
Opening Pressure Setting:
110.0 pounds per square inch
Material:
Steel stem
Media For Which Designed:
Water, fresh single response
Style Designator:
Angle
Thread Series Designator:
Not 1st and

Shelf Life:

Reference Number Differentiating Characteristics:

As differentiated by preset setting

N/a

NSN 4820-00-541-0924

Safety Relief Valve - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A046b0