## NSN 4820-00-541-1443

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-541-1443

Pipe Size Accommodated:
0.375 inches all ends
Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Bonnet Type:
Inside spring
Bonnet Attachment Method:
Threaded
Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
406.0 degrees fahrenheit single response
Connection Style:
Plain, optional en (pipe) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal pipe all ends
Features Provided:
Bonnet packing and pressure tight outlet side
Adjustable Pressure Range:
+10.0/+250.0 pounds per square inch
Maximum Operating Pressure:
250.0 pounds per square inch single response
Thread Size:
0.375 inches all ends
Material:
Steel stem
Material Specification:
Qq-c-390, alloy b5/d/ federal specification single material response body
Media For Which Designed:
Gas, natural 2nd response
Style Designator:
Angle
Thread Series Designator:
Npt all ends
Shelf Life:
OHOH EHO.

N/a

## NSN 4820-00-541-1443

Safety Relief Valve - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A046b0