NSN 4820-00-541-2298



Shuttle Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-541-2298 **Thread Class:** 3b all ends **Thread Direction:** Right-hand all ends Flow Control Device: Piston Valve Discharge Flow Rate: 1.2 gallons per minute **Maximum Operating Temp:** 160.0 degrees fahrenheit single response **Connection Style:** Flar (tube) all ends **Valve Operation Method:** Automatic **Connection Type:** Threaded internal tube all ends **Mounting Facility: Bracket Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches all ends **Outside Diameter Tube Accommodated:** 0.250 inches all ends **Special Features:** Over-all dim., 3.750 in. Lg, 1.062 in. W, 2.219 in. H, 2 mtg holes, 0.234 in. Id located on ea side of outlet port Material: Steel flow control device Media For Which Designed: Hydraulic fluid, phosphate-ester base single response **Surface Treatment:** Anodize **Style Designator:** Cross **Thread Series Designator:**

Unf all ends Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 4820-00-541-2298

Shuttle Valve - Page 2 of 2



Fiig:

A046b0