NSN 4820-00-541-2755

Safety Relief Valve - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4820-00-541-2755

| Pipe Size Accommodated: |
|--|
| 1.000 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Disk |
| Disk Loading Method: |
| Spring |
| Valve Discharge Flow Rate: |
| 32.0 cubic feet per minute |
| Maximum Operating Temp: |
| 400.0 degrees fahrenheit single response |
| Connection Style: |
| Plain (pipe) 1st end |
| Valve Operation Method: |
| Automatic or manual |
| Connection Type: |
| Threaded external pipe 1st end |
| Features Provided: |
| Pressure tight outlet side |
| Maximum Operating Pressure: |
| 160.0 pounds per square inch single response |
| Thread Size: |
| 1.000 inches 1st end |
| Opening Pressure Setting: |
| 15.0 pounds per square inch |
| Material: |
| Stainless steel stem |
| Media For Which Designed: |
| Gas, natural 2nd response |
| Style Designator: |
| Straight thru |
| Thread Series Designator: |
| Npt 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiia: |

A046b0