

View Online at <https://aerobasegroup.com/nsn/4820-00-541-3557>

Thread Direction:

Right-hand all ends

Flow Control Device:

Disk

Bonnet Type:

Inside screw

Bonnet Attachment Method:

Threaded

Maximum Operating Temp:

550.0 degrees fahrenheit 1st response

Connection Style:

Plain, optional en (pipe) all ends

Valve Operation Method:

Manual

Connection Type:

Threaded internal pipe all ends

Features Provided:

Bonnet packing

Maximum Operating Pressure:

400.0 pounds per square inch 2nd response

Thread Size:

0.125 inches all ends

Special Features:

Valve size 0.125 in.

Material:

Copper alloy 922

Material Specification:

Qq-c-390, alloy d4 federal specification all material responses

Media For Which Designed:

Water-oil-gas 2nd response

Style Designator:

Straight thru

Test Data Document:

81348-aww-v-51d specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Npt all ends

Specification Or Standard:

1 type and c class

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A046b0