

View Online at <https://aerobasegroup.com/nsn/4820-00-541-3557>

**Thread Direction:**

Right-hand all ends

**Flow Control Device:**

Disk

**Bonnet Type:**

Inside screw

**Bonnet Attachment Method:**

Threaded

**Maximum Operating Temp:**

550.0 degrees fahrenheit 1st response

**Connection Style:**

Plain, optional en (pipe) all ends

**Valve Operation Method:**

Manual

**Connection Type:**

Threaded internal pipe all ends

**Features Provided:**

Bonnet packing

**Maximum Operating Pressure:**

400.0 pounds per square inch 2nd response

**Thread Size:**

0.125 inches all ends

**Special Features:**

Valve size 0.125 in.

**Material:**

Copper alloy 922

**Material Specification:**

Qq-c-390, alloy d4 federal specification all material responses

**Media For Which Designed:**

Water-oil-gas 2nd response

**Style Designator:**

Straight thru

**Test Data Document:**

81348-aww-v-51d specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Npt all ends

**Specification Or Standard:**

1 type and c class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A046b0