NSN 4820-00-541-3568

Stop-lift-check Valve - Page 1 of 2

Flow Control Device:

Bonnet Attachment Method:

Bonnet Type: Exposed spring

Disk

Bolted



View Online at https://aerobasegroup.com/nsn/4820-00-541-3568

Disk Loading Method:
Spring
Renewable Seat Ring Type:
Threaded
Bolt Hole Quantity:
8 1st end
Valve Operation Method:
Manual
Flange Shape:
Round with holes 1st end
Connection Type:
Flange 1st end
Mounting Position:
Horizontal
Features Provided:
Bonnet packing
Valve Size:
3.000 inches
Outside Diameter:
6.625 inches 1st end
Face To Face Distance:
10.000 inches
Thickness:
0.500 inches 1st end
Bolt Hole Diameter:
0.562 inches 1st end
Bolt Circle Diameter:
5.500 inches 1st end
Flange Face Design:
Plain 1st end
Material:
Steel flow control device
Style Designator:
Angle flanged ends
Shelf Life:
N/a

NSN 4820-00-541-3568

Stop-lift-check Valve - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A530b0