NSN 4820-00-541-4030

Safety Relief Valve - Page 1 of 2

Thread Class: 3a all ends



View Online at https://aerobasegroup.com/nsn/4820-00-541-4030

Thread Direction:
Right-hand all ends
Flow Control Device:
Disk
Disk Loading Method:
Spring
Valve Discharge Flow Rate:
1.5 gallons per minute
Renewable Seat Ring Type:
Threaded
Maximum Operating Temp:
160.0 degrees fahrenheit single response
Connection Style:
Inverted flar (tube) all ends
Valve Operation Method:
Automatic
Connection Type:
Threaded internal tube all ends
Features Provided:
Pressure tight outlet side
Adjustable Pressure Range:
+350.0/+700.0 pounds per square inch
Maximum Operating Pressure:
400.0 pounds per square inch single response
Thread Size:
0.437 inches all ends
Seat Angle:
15.0 degrees all ends
Opening Pressure Setting:
400.0 pounds per square inch
Outside Diameter Tube Accommodated:
0.250 inches all ends
Material:
Stainless steel stem
Media For Which Designed:
Oil single response
Style Designator:
Angle
Thread Series Designator:
Unf all ends

NSN 4820-00-541-4030

Safety Relief Valve - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A046b0