## NSN 4820-00-541-4030

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-541-4030

**Thread Class:** 3a all ends **Thread Direction:** Right-hand all ends Flow Control Device: Disk **Disk Loading Method:** Spring Valve Discharge Flow Rate: 1.5 gallons per minute **Renewable Seat Ring Type:** Threaded Maximum Operating Temp: 160.0 degrees fahrenheit single response **Connection Style:** Inverted flar (tube) all ends Valve Operation Method: Automatic **Connection Type:** Threaded internal tube all ends **Features Provided:** Pressure tight outlet side Adjustable Pressure Range: +350.0/+700.0 pounds per square inch Maximum Operating Pressure: 400.0 pounds per square inch single response Thread Size: 0.437 inches all ends Seat Angle: 15.0 degrees all ends **Opening Pressure Setting:** 400.0 pounds per square inch **Outside Diameter Tube Accommodated:** 0.250 inches all ends Material: Stainless steel stem Media For Which Designed: Oil single response Style Designator: Angle **Thread Series Designator:** 

Unf all ends

## NSN 4820-00-541-4030

Safety Relief Valve - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A046b0

