NSN 4820-00-541-4995

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-541-4995

Pipe Size Accommodated:
1.250 inches 1st end
Flow Control Device:
Disk
Bonnet Type:
Exposed spring
Bonnet Attachment Method:
Union
Disk Loading Method:
Spring
Bolt Hole Quantity:
4 2nd end
Maximum Operating Temp:
250.0 degrees fahrenheit 1st response
Connection Style:
Socket with brazing ring err-100
Valve Operation Method:
Automatic
Flange Shape:
Round with holes 2nd end
Connection Type:
Unthreaded internal pipe 1st end
Adjustable Pressure Range:
+33.0/+53.0 pounds per square inch
Outside Diameter:
4.500 inches 2nd end
Thickness:
0.438 inches 2nd end
Bolt Hole Diameter:
0.562 inches 2nd end
Bolt Circle Diameter:
3.375 inches 2nd end
Flange Face Design:
Plain 2nd end
Material:
Nickel alloy flow control device
Style Designator:
Angle
Furnished Items And Quantity:
1 nut
Shelf Life:
N/a

NSN 4820-00-541-4995

Safety Relief Valve - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A046b0