

View Online at <https://aerobasegroup.com/nsn/4820-00-541-5700>

Flange Diameter:

15.000 inches

Bonnet Type:

Outside screw-yoke

Bonnet Attachment Method:

Bolted

Bolt Hole Quantity:

11

Valve Operation Method:

Manual

Connection Type:

Flange, round w/holes

Features Provided:

Bonnet packing

Valve Size:

10.000 inches

Stem Type:

Rising

Criticality Code Justification:

Feat

Face To Face Distance:

11.000 inches

Flange Face Design:

Plain

Inlet Relationship With Outlet:

Identical

Pressure Class:

250.0 pounds per square inch

Special Features:

Items are being coded as critical to insure source inspection will be performed at the point of manufacture, prior to material receipt by the us navy or other dod components. These items are piece parts or end items in support of vital military hardware necessary to sustain the successful mission of the ships, submarines, and shore stations of the us navy. Critical features including, but not limited to, dimensions, tolerances/clearances, electronic characteristics, and metallurgical properties will bespecified for government qar (quality assurance representatives) to insure the highest possible degree of quality and reliability of these parts being delivered under navicp contracts

Material:

Nickel alloy disk

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500a0