NSN 4820-00-541-6635

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-541-6635

	-
Thread Class:	
3a all ends	
Thread Direction:	
Right-hand all ends	
Flow Control Device:	
Poppet	
Bonnet Type:	
Packing retaining	
Valve Discharge Flow Rate:	
2.5 gallons per minute	
Maximum Operating Temp:	
200.0 degrees fahrenheit single response	
Connection Style:	
Flareless (tube) all ends	
Valve Operation Method:	
Automatic	
Connection Type:	
Threaded external tube all ends	
Features Provided:	
Pressure tight outlet side	
Maximum Operating Pressure:	
3550.0 pounds per square inch single response	
Thread Size:	
0.437 inches all ends	
Seat Angle:	
12.0 degrees all ends	
Opening Pressure Setting:	
3250.0 pounds per square inch	
Material:	
Aluminum alloy stem	
Media For Which Designed:	
Oil, hydraulic single response	
Style Designator:	
Straight thru	
Thread Series Designator:	
Unf all ends	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

No

NSN 4820-00-541-6635

Safety Relief Valve - Page 2 of 2

Fiig: A046b0

