NSN 4820-00-541-7659



Safety Relief Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4820-00-541-7659 **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end Flow Control Device: **Poppet Bonnet Type:** Packing retaining **Disk Loading Method:** Spring **Connection Style:** Gasket sea (boss) 1st end **Valve Operation Method:** Automatic **Connection Type:** Threaded internal boss 1st end **Features Provided:** Pressure tight outlet side Thready Qty Per Inch (tpi): 20 1st end **Adjustable Pressure Range:** +2300.0 to 3850.0 pounds per square inch **Maximum Operating Pressure:** 3000.0 pounds per square inch single response **Thread Size:** 0.437 inches 1st end **Outside Diameter Tube Accommodated:** 0.250 inches 1st end Media For Which Designed: Oil, hydraulic single response **Surface Treatment:** Anodize **Surface Treatment Specification:** Mil-a-8625, type 2 military specification single treatment response **Style Designator:** Err-090

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

NSN 4820-00-541-7659

Safety Relief Valve - Page 2 of 2



_		••	• •				
n	em	ш	112	riz	2 †1	n	٠.

No

Fiig:

A046b0

Mil-std (military Standard):

Mil-a-8625 spec.