NSN 4820-00-542-2028

Stop-check Valve - Page 1 of 2

Offset Distance:



View Online at https://aerobasegroup.com/nsn/4820-00-542-2028

2.250 inches
Flow Control Device:
Disk
Bonnet Type:
Outside screw-yoke
Bonnet Attachment Method:
Bolted
Disk Loading Method:
Weight
Renewable Seat Ring Type:
Threaded
Valve Operation Method:
Manual
Flange Shape:
Round 1st end
Connection Type:
Flange 1st end
Mounting Position:
Horizontal
Features Provided:
Bonnet packing
Valve Size:
1.500 inches
Maximum Operating Pressure:
600.0 pounds per square inch single response
Outside Diameter:
6.125 inches 1st end
6.125 inches 1st end Face To Face Distance:
Face To Face Distance:
Face To Face Distance: 12.000 inches
Face To Face Distance: 12.000 inches Thickness:
Face To Face Distance: 12.000 inches Thickness: 0.875 inches 1st end
Face To Face Distance: 12.000 inches Thickness: 0.875 inches 1st end Flange Face Design:
Face To Face Distance: 12.000 inches Thickness: 0.875 inches 1st end Flange Face Design: Raised straight 1st end
Face To Face Distance: 12.000 inches Thickness: 0.875 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height:
Face To Face Distance: 12.000 inches Thickness: 0.875 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.250 inches 1st end
Face To Face Distance: 12.000 inches Thickness: 0.875 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.250 inches 1st end Raised Face Diameter:
Face To Face Distance: 12.000 inches Thickness: 0.875 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.250 inches 1st end Raised Face Diameter: 2.875 inches 1st end
Face To Face Distance: 12.000 inches Thickness: 0.875 inches 1st end Flange Face Design: Raised straight 1st end Raised Face Height: 0.250 inches 1st end Raised Face Diameter: 2.875 inches 1st end Media For Which Designed:

NSN 4820-00-542-2028

Stop-check Valve - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A530b0