NSN 4820-00-542-4859

Globe Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-542-4859

1b 1st end Thread Direction: Right-hand 1st end Offset Distance: 0.688 inches Flow Control Device: Needle Bonnet Type: Outside screw-yoke Bonnet Attachment Method: Threaded Valve Operation Method: Manual Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Thready Size: 0.750 inches 1st end Seat Angle: 0.00 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: Na Unit Of Measure:	
Thread Direction: Right-hand 1st end Offset Distance: 0.688 inches Flow Control Device: Needle Bonnet Type: Outside screw-yoke Bonnet Attachment Method: Threaded Valve Operation Method: Manual Connection Type: Threaded internal tube 1st end Threaded jold inches 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Thread Class:
Right-hand 1st end Offset Distance: 0.688 Inches Flow Control Device: Needle Bonnet Type: Outside screw-yoke Bonnet Attachment Method: Threaded Valve Operation Method: Manual Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Naterial: Na Unit Of Measure: Unit Of Measure:	
Offset Distance: 0.688 inches Flow Control Device: Needle Bonnet Type: Outside screw-yoke Bonnet Attachment Method: Threaded Valve Operation Method: Manual Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Nature Unit Of Measure: Unit Of Measure: Unit Of Measure:	
Flow Control Device: Needle Bonnet Type: Outside screw-yoke Bonnet Attachment Method: Threadde Valve Operation Method: Manual Connection Type: Threaded Internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: Straight through wioffset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Sheff Life: Na Unit Of Measure:	•
Flow Control Device: Needle Bonnet Type: Outside screw-yoke Bonnet Attachment Method: Threaded Valve Operation Method: Manual Connection Type: Threaded internal tube 1st end Threaded internal tube 1st end Threaded internal tube 1st end Threads Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Offset Distance:
Needle Bonnet Type: Outside screw-yoke Bonnet Attachment Method: Threaded Valve Operation Method: Manual Connection Type: Threaded internal tube 1st end Threadd internal tube 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	0.688 inches
Bonnet Type: Outside screw-yoke Bonnet Attachment Method: Threaded Valve Operation Method: Manual Connection Type: Threaded internal tube 1st end Thready Oty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: 2zzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through widfset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Flow Control Device:
Dutside screw-yoke Bonnet Attachment Method: Threaded Valve Operation Method: Manual Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through wolfset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure: Interest Comp (1) Measure: Interest	Needle
Bonnet Attachment Method: Threaded Valve Operation Method: Manual Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Bonnet Type:
Threaded Valve Operation Method: Manual Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticallity Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Outside screw-yoke
Valve Operation Method: Manual Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Sheff Life: N/a Unit Of Measure:	Bonnet Attachment Method:
Manual Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Sheff Life: N/a Unit Of Measure:	Threaded
Connection Type: Threaded internal tube 1st end Thready Qty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Valve Operation Method:
Thready Qty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Manual
Thready Qty Per Inch (tpi): 16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Connection Type:
16 1st end Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Threaded internal tube 1st end
Thread Size: 0.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Thready Qty Per Inch (tpi):
O.750 inches 1st end Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	16 1st end
Seat Angle: 30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Thread Size:
30.0 degrees 1st end Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	0.750 inches 1st end
Criticality Code Justification: Zzzy Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Seat Angle:
Cutside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	30.0 degrees 1st end
Outside Diameter Tube Accommodated: 0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Criticality Code Justification:
0.375 inches 1st end Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Zzzy
Material: Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Outside Diameter Tube Accommodated:
Steel comp 316 Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	0.375 inches 1st end
Material Specification: 66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Material:
66 federal standard single material response Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Steel comp 316
Style Designator: Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Material Specification:
Straight through w/offset Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	66 federal standard single material response
Thread Series Designator: Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Style Designator:
Unf 1st end Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Straight through w/offset
Reference Number Differentiating Characteristics: As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Thread Series Designator:
As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications Shelf Life: N/a Unit Of Measure:	Unf 1st end
Shelf Life: N/a Unit Of Measure:	Reference Number Differentiating Characteristics:
Shelf Life: N/a Unit Of Measure:	As differentiated by material in accordance with activity hxquality control, manufacturing and testing specifications
Unit Of Measure:	Shelf Life:
	N/a
	Unit Of Measure:
Demilitarization:	<u></u>
	Demilitarization:
Ves - demil/mli	Yes - demil/mli

NSN 4820-00-542-4859

Globe Valve - Page 2 of 2



Fiig:

A046b0