NSN 4820-00-542-5822

Safety Relief Valve - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4820-00-542-5822

| Pipe Size Accommodated: |
|---|
| 0.500 inches 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Flow Control Device: |
| Disk |
| Bonnet Type: |
| Inside spring |
| Bonnet Attachment Method: |
| Threaded |
| Disk Loading Method: |
| Spring |
| Connection Style: |
| Plain (pipe) 1st end |
| Valve Operation Method: |
| Manual |
| Connection Type: |
| Threaded external pipe 1st end |
| Thready Qty Per Inch (tpi): |
| 14 1st end |
| Adjustable Pressure Range: |
| +4801.0/+6200.0 pounds per square inch |
| Maximum Operating Pressure: |
| 6200.0 pounds per square inch single response |
| Thread Size: |
| 0.500 inches 1st end |
| Special Features: |
| W/lifting lever |
| Material: |
| Copper alloy body |
| Style Designator: |
| Straight thru |
| Thread Series Designator: |
| Npt 1st end |
| Reference Number Differentiating Characteristics: |
| As differentiated by pac adsw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 4820-00-542-5822

Safety Relief Valve - Page 2 of 2



Fiig:

A046b0